

1 458A

ABSOLUTE MAXIMUM RATINGS

 $(T_A = 25^{\circ}C \text{ unless otherwise noted}) \text{ (Notes 1, 2, 3)}$

| Symbol | Rating | Value | Unit |
|--------------------|---------------------------------------------------------------------------------------------|-------------|------|
| V_{RRM} | Maximum Repetitive Reverse Voltage | 150 | V |
| I _{F(AV)} | Average Rectified Forward Current | 500 | mA |
| I _{FSM} | Non-repetitive Peak Forward Surge Current Pulse Width = 1.0 s Pulse Width = 1.0 µs | 1.0 4.0 | Α |
| T _{STG} | Storage Temperature Range | -65 to +200 | °C |
| TJ | Operating Junction Temperature | 175 | °C |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

- assumed, damage may occur and reliability may be affected.

 1. These ratings are limiting values above which the serviceability of the diode may be impaired.
- 2. These ratings are based on a maximum junction temperature of 200°C.
- 3. These are steady limits. The factory should be consulted on applications involving pulsed or low duty cycle operations.

THERMAL CHARACTERISTICS

Symbol

AXIAL LEAD CASE 017AG ISSUE O

DATE 31 AUG 2016



