
NOT RECO


# DISCONTINUED

CASE 318A






N <sub>1</sub> . 2. 3.	: <b>¼</b>	M A	A M	A :	A . A	14.5 , 1994.
4.	` Ā	A. A. N.,	A A B N	й .	A N 0.25	N BA A , N,
5. 6.	N N A	1 N N 0.3 NAA	. NA 25 A 1A BA	À A	_ A N A A A	- A N A A A A A A A A A A A A A A A A A
	DIM	MILLIN MIN	IETERS Max			
	A	0.80	1.12			
	A1	0.01	0.15			
	Ь	0.30	0.51			
	b1	0.76	0.94			
	С	0.08	0.20			
	D	2.80	3.05			
	E1	1 1 20	I 140 I			




b1	0.76	0.94
C	0.08	0.20
D	2.80	3.05
E1	1.20	1.40
е	1.92	В
e1	0.20	В
L	0.35	0.70
L2	0.25	В



(Note: Microdot may be in either location)

1: 1. 2. N N 3. 4. BA	2: 1. 2. NA 3. A 1 4. A 2	3: 1. 2. N. 3. N.
- 7: 1. 2. ¼` 3. A 4. ¼`	- 8: 1. 2. \$\frac{1}{A}\$. 4. /	9: 1. 2. 3. JA` 4. J






# CASE 527AH ISSUE A


DATE 09 JUN 2021





# CASE 527AJ ISSUE B

## DATE 29 FEB 2012









- NOTES:
  1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
  2. CONTROLLING DIMENSION: MILLIMETERS.
  3. DATUM C IS THE SEATING PLANE.

	MILLIMETERS			
DIM	MIN	MIN MAX		
Α		1.45		
A1	0.00	0.15		
A2	0.90	1.30		
b	0.20	0.50		
C	0.08	0.26		
D	2.70	3.00		
Е	2.50	3.10		
E1	1.30	1.80		
е	0.95 BSC			
L	0.20	0.60		
L2	0.25 BSC			



XXX= Specific Device Code

Μ = Date Code

= Pb-Free Package

(Note: Microdot may be in either location)

\*This information is generic. Please refer to device data sheet for actual part marking. Pb–Free indicator, "G" or microdot " ■", may or may not be present.

GENERIC
MARKING DIAGRAM\*

00000

