1 11

2- / /

Product Description

- --

1

CM1411

Table 1. PIN DESCRIPTIONS

Pin	Name	Description

CM1411

PERFORMANCE INFORMATION






WLCSP5, 0.94x1.41 CASE 567AZ-01 **ISSUE O**

DATE 26 JUL 2010

- NOTES:
 1. DIMENSIONING AND TOLERANCING PER
 ASME Y14.5M, 1994.
 2. CONTROLLING DIMENSION: MILLIMETERS.
 3. COPLANARITY APPLIES TO SPHERICAL
 CROWNS OF SOLDER BALLS.

	MILLIMETERS			
DIM	MIN	MAX		
Α	0.56	0.72		
A1	0.21	0.27		
A2	0.40 REF			
b	0.29	0.35		
D	0.94 BSC			
E	1.41 BSC			
eD	0.50 BSC			
еE	0.435 BSC			

RECOMMENDED SOLDERING FOOTPRINT*



DIMENSIONS: MILLIMETERS

*For additional information on our Pb–Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

PIN A1 REFERENCE	A B
2X 0.05 C TOP V	
OptiGuard C 0.05 C 0.05 C NOTE 3 A1 SIDE V	A
5x Ø b 0.05 C A B C 0.03 C B 1 2 BOTTOM	eD/2 eD eE N VIEW

DOCUMENT NUMBER:	98AON49809E	Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.	
DESCRIPTION:	WLCSP5, 0.94X1.41		PAGE 1 OF 1



