


FSGM0465R

Green-Mode Power Switch

Description

The FSGM0465R is an integrated Pulse Width Modulation (PWM) controller and SENSEFET[®] specifically designed for offline Switch-Mode Power Supplies (SMPS) with minimal external components. The PWM controller includes an integrated fixed-frequency oscillator, Under-Voltage Lockout (UVLO), Leading-Edge Blanking (LEB), optimized gate driver, internal soft-start, temperature-compensated precise current sources for loop compensation, and self-protection circuitry. Compared with a discrete MOSFET and PWM controller solution, the FSGM series can reduce total cost, component count, size, and weight; while simultaneously increasing efficiency, productivity, and system reliability. This device provides a basic platform suited for cost-effective design of a flyback converter.



Features

- Soft Burst-Mode Operation for Low Standby Power Consumption and Low Noise
- Precision Fixed Operating Frequency: 66 kHz
- Pulse-by-Pulse Current Limit
- Various Protection Functions: Overload Protection (OLP), Over-Voltage Protection (OVP), Abnormal Over-Current Protection (AOCP), Internal Thermal Shutdown (TSD) with Hysteresis, Output-Short Protection (OSP), and Under-Voltage Lockout (UVLO) with Hysteresis
- Auto-Restart Mode
- Internal Startup Circuit
- Internal High-Voltage SENSEFET: 650 V
- Built-in Soft-Start: 15 ms
- These are Pb-Free Devices

\$Y&Z&3&K
GM0465R

Applications

- Power Supply for LCD TV and Monitor, STB and DVD Combination

Related Resources

- [Power Supply WebDesigner — Flyback Design &ources](#)

FSGM0465R

ORDERING INFORMATION

| Part Number | Package | Operating Junction Temperature | Current Limit | R _{DS(ON)} (Max.) | Output Power Table (Note 2) | | | | Replaces Device | Shipping |
|---------------|--|--------------------------------|---------------|----------------------------|---------------------------------|---------------------|--------------------------|---------------------|-----------------|----------|
| | | | | | 230V _{AC} 15% (Note 3) | | 85 – 265 V _{AC} | | | |
| | | | | | Adapter (Note 4) | Open Frame (Note 5) | Adapter (Note 4) | Open Frame (Note 5) | | |
| FSGM0465RWDTU | TO-220F 6-Lead (Note 1) W-Forming | - | | | | | | | | |

FSGM0465R

Internal Block Diagram




Figure 2. Internal Block Diagram

FSGM0465R

PIN DEFINITIONS

| Pin No. | Name | Description |
|---------|------------------|--|
| 1 | Drain | . High-voltage power SENSEFET drain connection. |
| 2 | GND | . This pin is the control ground and the SENSEFET source. |
| 3 | V _{CC} | . This pin is the positive supply input, which provides the internal operating current for both startup and steady-state operation. |
| 4 | FB | . This pin is internally connected to the inverting input of the PWM comparator. The collector of an opto-coupler is typically tied to this pin. For stable operation, a capacitor should be placed between this pin and GND. If the voltage of this pin reaches 6 V, the overload protection triggers, which shuts down the power switch. |
| 5 | N.C. | No connection. |
| 6 | V _{STR} | . This pin is connected directly, or through a resistor, to the high-voltage DC link. At startup, the internal high-voltage current source supplies internal bias and charges the external capacitor connected to the V _{CC} pin. Once V _{CC} reaches 12 V, the internal current source (I _{CH}) is disabled. |

ABSOLUTE MAXIMUM RATINGS

| Symbol | Parameter | Min | Max | Unit |
|------------------|------------------------------|-----|-----|------|
| V _{STR} | V _{STR} Pin Voltage | - | 650 | |

FSGM0465R

THERMAL CHARACTERISTICS

| Symbol | Characteristic | Value | Unit |
|---------------|---|-------|------|
| θ_{JA} | Junction-to-Ambient Thermal Impedance (Note 11) | 62.5 | °C/W |
| θ_{JC} | Junction-to-Case Thermal Impedance (Note 12) | 3 | °C/W |

11. Infinite cooling condition

12. Free standing with no heat-sink under natural convection.

ELECTRICAL CHARACTERISTICS ($T_J = 25^\circ\text{C}$ unless otherwise noted)

| Symbol | Parameter | Test Condition | Min | Typ | Max | Unit |
|--------|-----------|----------------|-----|-----|-----|------|
|--------|-----------|----------------|-----|-----|-----|------|

SENSEFET SECTION

| | | | | | | |
|--------------|----------------------------------|---|-----|-----|-----|---------------|
| BV_{DSS} | Drain-Source Breakdown Voltage | $V_{CC} = 0\text{ V}, I_D = 250\ \mu\text{A}$ | 650 | - | - | V |
| I_{DSS} | Zero-Gate-Voltage Drain Current | $V_{DS} = 520\text{ V}, T_A = 125^\circ\text{C}$ | - | - | 250 | μA |
| $R_{DS(ON)}$ | Drain-Source On-State Resistance | $V_{GS} = 10\text{ V}, I_D = 1\text{ A}$ | - | 2.1 | 2.6 | Ω |
| C_{ISS} | Input Capacitance (Note 13) | $V_{DS} = 25\text{ V}, V_{GS} = 0\text{ V}, f = 1\text{ MHz}$ | - | 436 | - | pF |
| C_{OSS} | Output Capacitance (Note 13) | $V_{DS} = 25\text{ V}, V_{GS} = 0\text{ V}, f = 1\text{ MHz}$ | - | 65 | - | pF |
| t_r | Rise Time | $V_{DS} = 325\text{ V}, I_D = 4\text{ A}, R$ | | | | |

FSGM0465R

ELECTRICAL CHARACTERISTICS ($T_J = 25^\circ\text{C}$ unless otherwise noted) (continued)

| Symbol | Parameter | Test Condition | Min | Typ | Max | Unit |
|--------|-----------|----------------|-----|-----|-----|------|
|--------|-----------|----------------|-----|-----|-----|------|

PROTECTION SECTION

| | | | | | | | |
|---------------|--|------------------------|---|-----|-----|------------------|---------------|
| t_{OSP} | Output Short Protection (Note 13) | Threshold Time | OSP Triggered when $t_{ON} < t_{OSP}$ & $V_{FB} > V_{OSP}$ (Lasts Longer than t_{OSP_FB}) | 1.0 | 1.2 | 1.4 | μs |
| V_{OSP} | | Threshold V_{FB} | | 1.8 | 2.0 | 2.2 | V |
| t_{OSP_FB} | | V_{FB} Blanking Time | | 2.0 | 2.5 | 3.0 | μs |
| T_{SD} | Thermal Shutdown Temperature (Note 13) | Shutdown Temperature | 130 | 140 | 150 | $^\circ\text{C}$ | |

FSGM0465R

TYPICAL CHARACTERISTICS ($T_A = 25^\circ$)

FSGM0465R

TYPICAL CHARACTERISTICS ($T_A = 25^\circ$)

FUNCTIONAL DESCRIPTION

Startup

At startup, an internal high-voltage current source supplies the internal bias and charges the external capacitor

Protection Circuits

The FSGM0465R has several self-protective functions, such as Overload Protection (OLP), Abnormal Over-Current Protection (AOCP), Output-Short Protection (OSP), Over-Voltage Protection (OVP), and Thermal Shutdown (TSD). All the protections are implemented as auto-restart. Once the fault condition is detected, switching is terminated and the SENSEFET remains off. This causes V_{CC} to fall. When V_{CC} falls to the Under-Voltage Lockout (UVLO) stop voltage of 7.5 V, the protection is reset and the startup circuit charges the V_{CC} capacitor. When V_{CC} reaches the start voltage of 12.0 V, the FSGM0465R resumes normal operation. If the fault condition is not removed, the SENSEFET remains off and V_{CC} drops to stop voltage again. In this manner, the auto-restart can alternately enable and disable the switching of the power SENSEFET until the fault condition is eliminated. Because these protection circuits are fully integrated into the IC without external components, the reliability is improved without increasing cost.




Figure 19. Auto-Restart Protection Waveforms

Overload Protection (OLP)

Overload is defined as the load current exceeding its normal level due to an unexpected abnormal event. In this situation, the protection circuit should trigger to protect the SMPS. However, even when the SMPS is in normal operation, the overload protection circuit can be triggered during the load transition. To avoid this undesired operation, the overload protection circuit is designed to trigger only after a specified time to determine whether it is a transient situation or a true overload situation. Because of the pulse-by-pulse current limit capability, the maximum peak current through the SENSEFET is limited and, therefore, the maximum input power is restricted with a given input voltage. If the output consumes more than this maximum power, the output voltage (V_{OUT}) decreases below the set voltage. This reduces the current through the opto-coupler LED, which also reduces the opto-coupler transistor

current, thus increasing the feedback voltage (V_{FB}). If V_{FB} exceeds 2.4 V, D1 is blocked and the 3.3 μ A current source starts to charge C_{FB} slowly up. In this condition, V_{FB} continues increasing until it reaches 6.0 V, when the switching operation is terminated, as shown in Figure 20. The delay time for shutdown is the time required to charge C_{FB} from 2.4 V to 6.0 V with 3.3 μ A. A 25 ~ 50 ms delay is typical for most applications. This protection is implemented in auto-restart mode.




Figure 20. Overload Protection

Abnormal Over-Current Protection (AOCP)

When the secondary rectifier diodes or the transformer pins are shorted, the protection circuit is triggered. This protection circuit is implemented in auto-restart mode.

Output–Short Protection (OSP)

If the output is shorted, steep current with extremely high di/dt can flow through the SENSEFET during the minimum turn–on time. Such a steep current brings high–voltage stress on the drain of the SENSEFET when turned off. To protect the device from this abnormal condition, OSP is included. It is comprised of detecting V_{FB} and SENSEFET turn–on time. When the V_{FB} is higher than 2 V and the SENSEFET turn–on time is longer than 1.2 μ s, the FSGM0465R recognizes this condition as an abnormal error and shuts down PWM switching until V_{CC} reaches V_{START} again. An abnormal condition output short is shown in Figure 22.




Figure 22. Output–Short Protection

Over–Voltage Protection (OVP)

If the secondary–side feedback circuit malfunctions or a solder defect causes an opening in the feedback path, the current through the opto–coupler transistor becomes almost zero. Then V_{FB} climbs up in a similar manner to the overload situation, forcing the preset maximum current to be supplied to the SMPS until the overload protection is triggered. Because more energy than required is provided to the output, the output voltage may exceed the rated voltage before the overload protection is triggered, resulting in the breakdown of the devices in the secondary side. To prevent this situation, an OVP circuit is employed. In general, the V_{CC} is proportional to the output voltage and the FSGM0465R uses V_{CC} instead of directly monitoring the output voltage. If V_{CC} exceeds 24.5 V, an OVP circuit is triggered, resulting in the termination of the switching operation. To avoid undesired activation of OVP during normal operation, V_{CC} should be designed to be below 24.5 V.

Thermal Shutdown (TSD)

The SENSEFET and the control IC on a die in one package makes it easier for the control IC to detect the over temperature of the SENSEFET. If the temperature exceeds $\sim 140^{\circ}\text{C}$, the thermal shutdown is triggered and the FSGM0465R stops operation. The FSGM0465R operates in auto–restart mode until the temperature decreases to around 110°C , when normal operation resumes.

Soft Burst–Mode Operation

To minimize power dissipation in standby mode, the FSGM0465R enters burst–mode operation. As the load decreases, the feedback voltage decreases. As shown in Figure 23, the device automatically enters burst mode when the feedback voltage drops below V_{BURL} (500 mV). At this point, switching stops and the output voltages start to drop at a rate dependent on standby current load. This causes the feedback voltage to rise. Once it passes V_{BURH} (700 mV), switching resumes. At this point, the drain current peak increases gradually. This soft burst–mode can reduce audible noise during burst–mode operation. The feedback voltage then falls and the process repeats. Burst–mode operation alternately enables and disables switching of the SENSEFET, thereby reducing switching loss in standby mode.




Figure 23. Burst–Mode Operation

FSGM0465R

TYPICAL APPLICATION CIRCUIT

Table 2. TYPICAL APPLICATION CIRCUIT


| Application | Input Voltage | Rated Output | Rated Power |
|------------------------------|--------------------------|-------------------------------|-------------|
| LCD TV, Monitor Power Supply | 85 ~ 265 V _{AC} | 5.0 V (2 A) 14.0 V (2.4 A) | 43.6 W |

Key Design Notes:

1. The delay time for overload protection is designed to be about 30 ms with C105 (27 nF). OLP time between 25 ms (22 nF) and 50 ms (43 nF) is recommended.

2. The SMD-type capacitor (C106) must be placed as close as possible to the V_{CC} pin to avoid malfunction by abrupt pulsating noises and to improve ESD and surge immunity. Capacitance between 100 nF and 220 nF is recommended.

Schematic



Winding Specification

Table 3. WINDING SPECIFICATION

| | Pin (S F) | Wire | Turns |
|--|-----------|------|-------|
|--|-----------|------|-------|

FSGM0465R

Bill of Materials


Table 5. Bill of Materials

| Part # | Value | Note |
|-----------------|--------------------|------------------|
| Fuse | | |
| F101 | 250 V 3.15 A | |
| NTC | | |
| NTC101 | 5D-9 | DSC |
| Resistor | | |
| R101 | 1.5 M Ω , J | 1 W |
| R102 | 75 k Ω , J | 1/2 W |
| R103 | 43 k Ω , J | 1 W |
| R104 | 62 Ω , J | 1/2 W |
| R201 | 330 Ω , F | 1/4 W, 1% |
| R202 | 1.2 k Ω , F | 1/4 W, 1% |
| R203 | 18 k Ω , F | 1/4 W, 1% |
| R204 | 8 k Ω , F | 1/4 W, 1% |
| R205 | 8 k Ω , F | 1/4 W, 1% |
| IC | | |
| FSGM0465R | FSGM0465R | ON Semiconductor |
| IC201 | KA431LZ | ON Semiconductor |
| IC301 | FOD817B | ON Semiconductor |
| Diode | | |
| D101 | 1N4007 | Vishay |
| D102 | UF4004 | Vishay |
| ZD101 | 1N4749 | Vishay |
| D201 | MBR20150CT | ON Semiconductor |
| D202 | FYPF2006DN | ON Semiconductor |
| BD101 | G2SBA60 | Vishay |

| Part # | Value | Note |
|------------------|---------------------|-------------------------|
| Capacitor | | |
| C101 | 220 nF / 275 V | Box (Pilkor) |
| C102 | 150 nF / 275 V | Box (Pilkor) |
| C103 | 100 μ F / 400 V | Electrolytic (SamYoung) |
| C104 | 3.3 nF / 630 V | Film (Sehwa) |
| C105 | 27 nF / 100 V | Film (Sehwa) |
| C106 | 220 nF | SMD (2012) |
| C107 | 47 μ F / 50 V | Electrolytic (SamYoung) |
| C201 | 1000 μ F / 25 V | Electrolytic (SamYoung) |
| C202 | 1000 μ F / 25 V | Electrolytic (SamYoung) |
| C203 | 2200 μ F / 10 V | Electrolytic (SamYoung) |
| C204 | 1000 μ F / 16 V | Electrolytic (SamYoung) |
| C205 | 47 nF / 100 V | Film (Sehwa) |
| C206 | 100 nF | SMD (2012) |
| C207 | 100 nF | SMD (2012) |
| C301 | 4.7 nF / Y2 | Y-cap (Samhwa) |
| Inductor | | |
| LF101 | 15 mH | |

TO-220-6LD LF
CASE 340BG
ISSUE A

DATE 01 SEP 2021



onsemi, **onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi**
