Typical Applications

- Switching Power Supplies including Wireless, Notebook Adapters
- High Frequency and DC-DC Converters
- Freewheeling and OR-ing diodes
- Reverse Battery Protection
- Instrumentation
- Automotive LED Lighting

Mechanical Characteristics:

- Case: Epoxy, Molded
- Epoxy Meets Flammability Rating UL 94-0 @
- Lead Finish: 100% Matte Sn (Tin)
- Lead and Mounting Surface Temperature for S 260°C Max. for 10 Seconds
- Device Meets MSL 1 Requirements
- Mass Approximately 25 mg


 Mass Approximately 25 mg

DEVIG-PLEASENTATIVE FOR




THIS DEVI


١



	MILLIMETERS		
DIM	MIN	NOM	MAX
Α	0.70	0.75	0.80
A1	0.00	-	0.05
b	0.23	0.30	0.40
С	0.15	0.20	0.25
D			
D1	2.95	3.05	3.15
D2	1.98	2.11	2.24
E			
E1	2.95	3.05	3.15
E2	1.47	1.60	1.73
е		0.65 BSC	;
G	0.30	0.41	0.51
K	0.65	0.80	0.95
L	0.30	0.43	0.56
L1	0.06	0.13	0.20



SOLDERING FOOTPRINT*ellt:(TD().80)TETq



*For additional information on our Pb–Free strategy and soldering details, please download the **onsemi** Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

and ONSEMI. are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

